

CL CO-LO ENCLOSURE



The Co-Lo provides separate entry for each compartment; approved personnel are able to access the necessary equipment, while the remaining equipment is protected from unauthorized use.

- Pre-assembled to your equipment configuration
- Secure vertical cable management raceways
- Cable access provisions located on top and bottom
- Grounding studs on doors, side panels, and base unit
- Fan assembly located on each rear door optional

DIMENSIONS: 2134mmH x (600 or 800mmW) x 1000mmD
Maximum rail placement and usable inside depth: 950mm

RACK SPACES: 14 RMU per compartment • 19" EIA 310-E Compliant

COLOR: Black RAL 9500

WEIGHT CAPACITY: 680 kg. on levelers or bolted to floor

SHIPPING WEIGHT: 227 kg.

PART NO.	DESCRIPTION
GL14CL3MM	800mmW, 3 compartment Co-Lo Enclosure (14 RMU per compartment) with mesh front and rear doors; secure vertical cable management raceways (rear raceway, 1384mmH x 146mmW x 70mmD; front raceway 724mmH x 146mmW x 70mmD); grounding studs on doors, side panels, and frame
GL14CL3PF	Same as GL14CL3MM except with perimeter vented plexi front doors and solid rear doors with built in exhaust fans
GL14CL3MM-600	600mmW, 3 compartment Co-Lo Enclosure (14 RMU per compartment) with mesh front and rear doors; secure vertical cable management raceways (rear raceway, 1384mmH x 146mmW x 70mmD; front raceway 724mmH x 146mmW x 70mmD); grounding studs on doors, side panels, and frame
GL14CL3PF-600	Same as GL14CL3MM-600 except with perimeter vented plexi front doors and solid rear doors with built in exhaust fans

ACCESSORIES

PART NO.	DESCRIPTION
7206-350	Stationary Shelf, front/rear mount adjustable, 445mmW x 355mmD, 36 kg. weight capacity
CM-04	Interbay Cable Organizer with 4 front horizontal rings, 83mmW x 71mmD
CBB-19	Copper Bus Bar for 19" mounting (isolated)
GR101	Grounding Kit
AK101	Seismic Anchor Kit (includes 4 torque controlled expansion anchors)
7208-E	One Set of 4 Casters, 2 locking and 2 non-locking
7209-N	One Set of 4 Adjustable Levelers (64mmH)
CH-02	Door Handle with three digit combination and key



Shown with optional accessories.
Drawings can be found on 173

CO-LO ENCLOSURE CL



The Co-Lo provides separate entry for each compartment; approved personnel are able to access the necessary equipment, while the remaining equipment is protected from unauthorized use.

- Pre-assembled to your equipment configuration
- Secure vertical cable management raceways
- Cable access provisions located on top and bottom
- Grounding studs on doors, side panels, and base unit
- Fan assembly located on each rear door optional

DIMENSIONS: 2134mmH x (600 or 800mmW) x 1000mmD
Maximum rail placement and usable inside depth: 950mm

RACK SPACES: 21 RMU per compartment • 19" EIA 310-E Compliant

COLOR: Black RAL 9500

WEIGHT CAPACITY: 680 kg. on levelers or bolted to floor

SHIPPING WEIGHT: 227 kg.

PART NO.	DESCRIPTION
GL21CL2MM	Complete 2 compartment Co-Lo Enclosure (21 RMU per compartment) with mesh front and rear doors; secure vertical cable management raceways (1127mmH x 146mmW x 70mmD)
GL21CL2PF	Same as GL21CL2MM except with perimeter vented plexi front doors and solid rear doors with built in exhaust fans
GL21CL2MM-600	Complete 2 compartment Co-Lo Enclosure (21 RMU per compartment) with mesh front and rear doors; secure vertical cable management raceways (1127mmH x 146mmW x 70mmD)
GL21CL2PF-600	Same as GL21CL2MM-600 except with perimeter vented plexi front doors and solid rear doors with built in exhaust fans

ACCESSORIES

PART NO.	DESCRIPTION
7206-350	Stationary Shelf, front/rear mount adjustable, 445mmW x 355mmD, 36 kg. weight capacity
CM-04	Interbay Cable Organizer with 4 front horizontal rings, 83mmW x 71mmD
CBB-19	Copper Bus Bar for 19" mounting (isolated)
GR101	Grounding Kit
AK101	Seismic Anchor Kit (includes 4 torque controlled expansion anchors)
7208-E	One Set of 4 Casters, 2 locking and 2 non-locking
7209-N	One Set of 4 Adjustable Levelers (64mmH)
CH-02	Door Handle with three digit combination and key



Shown with optional accessories.
Drawings can be found on 173