

IP 52 ENCLOSURE



Hinge and Gasketing

Heavy Duty Handle with 3 point latch



Optional Fan Assembly (includes filter)



Optional Ice Qube Vertical Mount AC Unit; installs by removing two gland plates from enclosure

Cable Access Knockouts



Drawings can be found on page 98



Great Lakes' IP 52 Free Standing Enclosures are constructed to be compliant with the International Protection Rating standard. IP 52 enclosures are intended for indoor use to provide a degree of protection to the equipment inside the enclosure against dust, falling dirt, water and non-corrosive liquids. These enclosures are also intended to provide a degree of protection to personnel against access to hazardous parts which may be mounted within the enclosure.

PART NO.

DESCRIPTION

GL45N12-6000

IP 52 Enclosure; Dimensions 2134mmH x 610mmW x 1000mmD, 45 RMU, Weight Capacity 907 kg.

ACCESSORIES

PART NO.

DESCRIPTION

FFKN12-B1

Fan Assembly (includes filter) and exhaust filter, 505 CMHr, 230V

FFKN12-B2

Fan Assembly (includes filter) and exhaust filter, 625 CMHr, 230V

FFKN12-B3

Fan Assembly (includes filter) and exhaust filter, 785 CMHr, 230V

FILTER-09

Package of five replacement filters for fan kits

Each Ice Qube AC Unit is UL listed and has a digital temperature controller with alarm, built in condensate evaporator, and contains CFC-free refrigerant.

Ice Qube AC Units are warranted by Ice Qube for a period of 1 Year from invoice date.

GL2500V

Ice Qube AC Unit, 2500 BTU, 230V, 3.5/3.9 amps

GL3500V

Ice Qube AC Unit, 3500 BTU, 230V, 4.3/4.7amps

GL4500V

Ice Qube AC Unit, 4500 BTU, 230V, 4.6/5.1 amps

