



SPECIFICATIONS:

RACK SPACES : 19" EIA 310-E COMPLIANT - SEE CHART

WEIGHT CAPACITY : 680 kg 37RMU & GREATER / 272 kg 31RMU & LOWER (BOLTED TO FLOOR, LEVELERS, OR ON CASTERS.)

COLOR : DURABLE TEXTURED BLACK POWDER COATING

CERTIFICATIONS : UL 60950-1 STANDARD FOR I.T. & COMMUNICATIONS EQUIPMENT.

CONSTRUCTION : 2 PAIR MOUNTING RAILS , 2.5mm THK C.R.S. FULLY WELDED FRAME, 1.5mm THK C.R.S. DOORS, SIDE PANELS, TOP PANEL, 1.5mm THK C.R.S.

HARDWARE : PACKAGE OF QTY-50; M6 SCREWS AND CAGE NUTS, INCLUDED.

PART NUMBER	H - HEIGHT	W - WIDTH	D - DEPTH	RMU - TOTAL
GL44E-60100	2134	600	1000	44 RMU
GL44E-6080	2134	600	800	44 RMU
GL41E-80100	1981	800	1000	41 RMU
GL41E-8080	1981	800	800	41 RMU
GL41E-60100	1981	600	1000	41 RMU
GL41E-6080	1981	600	800	41 RMU
GL41E-6060	1981	600	600	41 RMU
GL37E-60100	1829	600	1000	37 RMU
GL37E-6080	1829	600	800	37 RMU
GL37E-6060	1829	600	600	37 RMU
GL31E-60100	1524	600	1000	31 RMU
GL31E-6080	1524	600	800	31 RMU
GL31E-6060	1524	600	600	31 RMU
GL24E-60100	1219	600	1000	24 RMU
GL24E-6080	1219	600	800	24 RMU
GL24E-6060	1219	600	600	24 RMU
GL13E-6080	762	600	800	13 RMU
GL13E-6060	762	600	600	13 RMU